APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/790,894	03/01/2004	Mary Morabito O'Neill	03W179	2583

7590   07/24/2008

Raytheon Company
2000 East El Segundo Boulevard, EO/E04/N119
P.O. Box 902
El Segundo, CA 90245

EXAMINER
WYATT, KEVIN S

ART UNIT	PAPER NUMBER
2878	

MAIL DATE	DELIVERY MODE
07/24/2008	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
	10/790,894	O'NEILL ET AL.
Office Action Summary	Examiner	Art Unit	
	Kevin Wyatt	2878	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE <u>3</u> MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1) ☒ Responsive to communication(s) filed on <u>31 March 2008</u>.

2a) ☐ This action is **FINAL**.   2b) ☒ This action is non-final.

3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4) ☒ Claim(s) <u>1-24</u> is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5) ☐ Claim(s) _____ is/are allowed.

6) ☒ Claim(s) <u>1-24</u> is/are rejected.

7) ☐ Claim(s) _____ is/are objected to.

8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9) ☐ The specification is objected to by the Examiner.

10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a) ☐ All   b) ☐ Some * c) ☐ None of:

      1. ☐ Certified copies of the priority documents have been received.

      2. ☐ Certified copies of the priority documents have been received in Application No. _____.

      3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)

2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3) ☐ Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date _____.

4) ☐ Interview Summary (PTO-413) Paper No(s)/Mail Date. _____

5) ☐ Notice of Informal Patent Application

6) ☐ Other: _____.

DETAILED ACTION

1.   This Office Action is in response to the Amendment after non-final and remarks

filed on 03/31/2008. Currently, claims 1-24 are pending.

Claim Rejections - 35 USC § 102

2.   The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that

form the basis for the rejections under this section made in this Office action:

> A person shall be entitled to a patent unless –
>
> (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

3.   Claims 1-2, 8-14, 20-24 are rejected under 35 U.S.C. 102(b) as being anticipated

by Vock (U.S. Patent No. 6,320,173 B1).

        Regarding claim 1, Vock shows in Fig. 6A-B a method for locating a position of a

feature in a scene, comprising the steps of forming an image (120, 142e, 152 or 154) of

the feature using a segmented array (132, 140 or 150) having a plurality of array

subelements each having a linear dimension, wherein each of the array subelements

has an output signal (col. 7, lines 33-40); and cooperatively analyzing the output signals

from at least two spatially adjacent array subelements to establish a data set reflective

of an extent to which output signals responsive to the image of the feature are produced

from exactly one or from more than one of the adjacent array subelements, and to reach

a conclusion from the data set as to a location of the image of the feature on the

segmented array with an accuracy of less than the linear dimension of an array

subelements when the output signal is produced from more than one of the adjacent

array subelements (col. 3, 13-25 and col. 7, lines 33-40).

Regarding claim 2, Vock shows in Figs. 2, 4-6, a method wherein the step of forming includes the step of providing a sensor (40, i.e., solid state camera, 132, i.e., focal plane elements or 108, i.e., array of elements) including an optics system (42, 71,102 and 130) that forms the image of the feature of the scene at an image surface (focal plane), and the segmented array at the image surface upon which the image is formed.

Regarding claim 8, Vock shows in Figs. 4-6, a method wherein the step of providing a sensor includes the step of providing a two-dimensional segmented array (108, 140 or 150).

Regarding claim 9, Vock shows in Figs. 4-6, a method wherein the step of providing a sensor includes the step of providing a two-dimensional segmented array formed of a pattern of intersecting array subelements (108, 140 or 150).

Regarding claim 10, Vock discloses a method wherein the step of cooperatively analyzing includes the steps of determining whether output signals responsive to the image of the feature are produced in single ones or combinations of the intersecting array subelements, and identifying the location of the image of the feature responsive to a distribution of the output signals from the step of determining whether output signals responsive to the image of the feature are produced in the intersecting array subelements (col. 3, 13-25 and col. 7, lines 33-40).

Regarding claim 11, Vock discloses a method wherein the step of cooperatively analyzing includes the steps of determining the relative strengths of the output signals

responsive to the image of the feature that are produced in combinations of the intersecting array subelements, and identifying the location of the image of the feature responsive to the relative strengths of the output signals from the step of determining the relative strengths of the output signals responsive to the image of the feature that are produced in combinations of the intersecting array subelements (col. 12, lines 49-60 and col. 13, lines 1-6).

Regarding claim 12, Vock shows in Figs. 6A-B a method wherein the step of providing a sensor (140 or 150) includes the step of providing a two-dimensional segmented array formed of a pattern of square array subelements, wherein four of the square array subelements meet at an intersection point, and wherein the step of forming an image includes the step of forming the image having a diameter of one blur diameter (the slightly blurred image of 142a-e, 152 or 154).

Regarding claim 13, Vock discloses a method for locating a position of a feature in a scene, comprising the steps of forming an image of the feature using a segmented light-detector array having a plurality of light-detector subelements, wherein each of the light-detector subelements has an output signal (col. 3, 13-25 and col. 7, lines 33-40); and cooperatively analyzing the output signals from at least two spatially adjacent light-detector subelements to establish a data set reflective of an extent to which output signals responsive to the image of the feature are produced from exactly one or from more than one of the adjacent light-detector subelements, and to reach a conclusion from the data set as to a location of the image of the feature on the segmented light-detector array (col. 3, 13-25 and col. 7, lines 33-40).

Regarding claim 14, Vock shows in Figs. 2, 4-6, a method wherein the step of forming includes the step of providing a sensor (40, i.e., solid state camera, 132, i.e., focal plane elements or 108, i.e., array of elements) including an optics system (42, 71,102 and 130) that forms the image of the feature of the scene at an image surface, and the segmented light-detector array at the image surface upon which the image is formed.

Regarding claim 20, Vock shows in Figs. 2, 4-6, wherein the step of providing a sensor includes the step of providing a two-dimensional segmented light-detector array.

Regarding claim 21, Vock shows in Figs. 2, 4-6, wherein the step of providing a sensor includes the step of providing a two-dimensional segmented light-detector array formed of a pattern of intersecting light-detector subelements.

Regarding claim 22, Vock discloses a method wherein the step of cooperatively analyzing includes the steps of determining whether output signals responsive to the image of the feature are produced in single ones or combinations of the intersecting light-detector subelements, and identifying the location of the image of the feature responsive to a distribution of the output signals from the step of determining whether output signals responsive to the image of the feature are produced in the intersecting light-detector subelements (col. 3, 13-25 and col. 7, lines 33-40).

Regarding claim 23, Vock discloses a method wherein the step of cooperatively analyzing includes the steps of determining the relative strengths of the output signals responsive to the image of the feature that are produced in combinations of the intersecting light-detector subelements, and identifying the location of the image of the

feature responsive to the relative strengths of the output signals from the step of

determining the relative strengths of the output signals responsive to the image of the

feature that are produced in combinations of the intersecting light-detector subelements

(col. 12, lines 49-60 and col. 13, lines 1-6).

Regarding claim 24, Vock shows in Figs. 6A-B a method for locating a position of

a feature in a scene, comprising the steps of forming an image (120, 142e, 152 or 154)

having a diameter of about one blur diameter (the slightly blurred image of 142a-e, 152

or 154) of the feature using a two-dimensional segmented array (132, 140 or 150)

having a plurality of square array subelements, wherein four of the square array

subelements meet at an intersection point, and wherein each of the array subelements

has an output signal (col. 7, lines 33-40); and cooperatively analyzing the output signals

from at least two spatially adjacent array subelements to establish a data set reflective

of an extent to which output signals responsive to the image of the feature are produced

from exactly one or from more than one of the adjacent array subelements, and to reach

a conclusion from the data set as to a location of the image of the feature on the

segmented array (col. 3, 13-25 and col. 7, lines 33-40).

Claim Rejections - 35 USC § 103

4.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set
> forth in section 102 of this title, if the differences between the subject matter sought to be patented and
> the prior art are such that the subject matter as a whole would have been obvious at the time the
> invention was made to a person having ordinary skill in the art to which said subject matter pertains.
> Patentability shall not be negatived by the manner in which the invention was made.

5.   Claims 1-6, and 13-18 are rejected under 35 U.S.C. 103(a) as being

unpatentable over Perregaux (U.S. Patent No. 6,654,056 B1) in view of Ang (U.S.

Patent No. 6,507,011 B2).

         Regarding claim 1, Perregaux discloses, a method for locating a position of a

feature in a scene (document), comprising the steps of forming an image of the feature

using a segmented array (10, i.e., photosensitive chip) having a plurality of array

subelements (100, i.e., photosite), each having a linear dimension wherein each of the

array subelements has an output signal. Perregaux does not explicitly disclose

cooperatively analyzing the output signals from at least two spatially adjacent array

subelements to establish a data set reflective of an extent to which output signals

responsive to the image of the feature are produced from exactly one or from more than

one of the adjacent array subelements and to reach a conclusion from the data set as to

a location of the image of the feature on the segmented array with an accuracy of less

than the linear dimension of an array subelement when the output signal is produced

from one or more than one of the adjacent array subelements. However, determining

feature locations and cooperatively analyzing adjacent array subelements, for document

generation or document reproduction devices such as digital scanners, copiers and

facsimile machines would be routinely performed by any appropriate software or

microprocessing function within the device in order to convert and place the detected

signals in the proper location in the device's memory. For example, the microprocessing

functions performed by the "CMOS active pixel color linear image sensor" in Fig. 3 of

Ang (U.S. Patent No. 6,507,011 B2) such as line control/readout logic circuit (320), line

store select logic (330), timing control circuit (370) and analog mux (350). It would have been obvious to one skilled in the art to provide a device capable of cooperatively analyzing adjacent array subelements and determining feature locations for the purpose of reconstructing (from memory) the imaged feature for image reproduction.

Regarding claim 13, Perregaux discloses a method for locating a position of a feature in a scene (document), comprising the steps of forming an image of the feature using a segmented light-detector array (10, i.e., photosensitive chip) having a plurality of light-detector subelements (100, i.e., photosite) each having a linear dimension, wherein each of the light-detector subelements has an output signal; and cooperatively analyzing the output signals from at least two spatially adjacent light-detector subelements to establish a data set reflective of an extent to which output signals responsive to the image of the feature are produced from exactly one or from more than one of the adjacent light-detector subelements, and to reach a conclusion from the data set as to a location of the image of the feature on the segmented light-detector array with an accuracy of less than the linear dimension of an array subelement when the output signal is produced from one or more than one of the adjacent array subelements However, determining feature locations and cooperatively analyzing adjacent array subelements, for document generation or document reproduction devices such as digital scanners, copiers and facsimile machines would be routinely performed by any appropriate software or microprocessing function within the device in order to convert and place the detected signals in the proper location in the device's memory. For example, the microprocessing functions performed by the "CMOS active pixel color

linear image sensor" in Fig. 3 of Ang (U.S. Patent No. 6,507,011 B2) such as line
control/readout logic circuit (320), line store select logic (330), timing control circuit (370)
and analog mux (350). It would have been obvious to one skilled in the art to provide a
device capable of cooperatively analyzing adjacent array subelements and determining
feature locations for the purpose of reconstructing (from memory) the imaged feature for
image reproduction.

Regarding claim 2, Perregaux further discloses, the step of forming includes the
step of providing a sensor including an optics system (located within the raster input
scanner (RIS)) that forms the image of the feature of the scene (document) at an image
surface, and the segmented array at the image surface upon which the image is formed
(col. 14, lines 5-7).

Regarding claims 3, Perregaux further shows in Fig. 4 the step of providing a
sensor (10, i.e., photosensitive chip) includes the step of providing a one-dimensional
segmented array formed of pairs of two adjacent array subelements (100, i.e.,
photosites).

Regarding claim 4, Perregaux further discloses the step of cooperatively
analyzing includes the steps of determining whether output signals responsive to the
image of the feature are produced by one or both of the two adjacent array subelements
(the function of the raster input scanner (RIS), col. 14, lines 9-11), and identifying the
location of the image of the feature (document) responsive to the step of determining
whether output signals responsive to the feature are produced by one or both of the two
adjacent array subelements (col. 14, lines 9-11) (col. 14, lines 28-36).

Regarding claim 5, Perregaux further discloses the step of cooperatively analyzing includes the steps of determining relative strengths of output signals responsive to the feature produced by the two adjacent array subelements, and identifying the location of the image of the feature responsive to the step of determining relative strengths of output signals responsive to the feature (col. 14, lines 28-36).

Regarding claim 6, Perregaux further shows in Fig. 4, the step of providing a sensor includes the step of providing a one-dimensional segmented array having spatially overlapping array subelements.

Regarding claim 14, Perregaux further discloses the step of forming includes the step of providing a sensor including an optics system that forms the image of the feature of the scene at an image surface, and the segmented light-detector array at the image surface upon which the image is formed.

Regarding claim 15, Perregaux further shows in Fig. 4 the step of providing a sensor includes the step of providing a one-dimensional segmented light-detector array formed of pairs of two adjacent light-detector subelements.

Regarding claim 16, Perregaux discloses wherein the step of cooperatively analyzing includes the steps of determining whether output signals responsive to the image of the feature are produced by one or both of the two adjacent light-detector subelements (the function of the raster input scanner (RIS), col. 14, lines 9-11), and identifying the location of the image of the feature responsive to the step of determining whether output signals responsive to the feature are produced by one or both of the two adjacent light-detector subelements (col. 14, lines 9-11) (col. 14, lines 28-36).

Regarding claim 17, the step of cooperatively analyzing includes the steps of

determining relative strengths of output signals responsive to the feature produced by

the two adjacent light-detector subelements, and identifying the location of the image of

the feature responsive to the step of determining relative strengths of output signals

responsive to the feature (col. 14, lines 28-36).

Regarding claim 18, Perregaux shows in Fig. 4 the step of providing a sensor

includes the step of providing a one-dimensional segmented light-detector array having

spatially overlapping light-detector subelements.

6.   Claims 1-2, 7, 13 and 19 are rejected under 35 U.S.C. 103(a) as being

unpatentable over Hou (U.S. Patent No. 6,596,979 B2) in view of Ang (U.S. Patent No.

6,507,011 B2).

Regarding claim 1, Hou shows in Figs. 2A-2B, 3 and 10, a method for locating a

position of a feature in a scene, comprising the steps of forming an image of the feature

using a segmented array having a plurality of array subelements, wherein each of the

array subelements has an output signal (col. 5, lines 27-35). Hou does not explicitly

disclose cooperatively analyzing the output signals from at least two spatially adjacent

array subelements to establish a data set reflective of an extent to which output signals

responsive to the image of the feature are produced from exactly one or from more than

one of the adjacent array subelements each having a linear dimension, and to reach a

conclusion from the data set as to a location of the image of the feature on the

segmented array with an accuracy of less than the linear dimension of an array

subelement when the output signal is produced from one or more than one of the

adjacent array subelements. However, determining feature locations and cooperatively

analyzing adjacent array subelements, for document generation or document

reproduction devices such as digital scanners, copiers and facsimile machines would be

routinely performed by any appropriate software or microprocessing function within the

device in order to convert and place the detected signals in the proper location in the

device's memory. For example, the microprocessing functions performed by the "CMOS

active pixel color linear image sensor" in Fig. 3 of Ang (U.S. Patent No. 6,507,011 B2)

such as line control/readout logic circuit (320), line store select logic (330), timing

control circuit (370) and analog mux (350).. It would have been obvious to one skilled in

the art to provide a device capable of cooperatively analyzing adjacent array

subelements and determining feature locations for the purpose of reconstructing (from

memory) the imaged feature for image reproduction.

Regarding claim 2, Hou shows in Figs. 2A-2B, 3 and 10, the step of forming

includes the step of providing a sensor including an optics system (208, i.e., rod lens

array or 274, i.e., optical lens) that forms the image of the feature of the scene at an

image surface (250, i.e., photodetector array or 276, i.e., image sensor), and the

segmented array at the image surface upon which the image is formed.

Regarding claim 7, Hou shows in Fig. 10, the step of providing a sensor includes

the step of providing a one-dimensional segmented array (performs the function of a

one-dimensional array) having non-spatially overlapping array subelements.

Regarding claim 13, Hou shows in Fig. 10, a method for locating a position of a

feature in a scene, comprising the steps of forming an image of the feature using a

segmented light-detector array having a plurality of light-detector subelements each
having a linear dimension, wherein each of the light-detector subelements has an output
signal (col. 5, lines 27-35). Hou does not explicitly disclose cooperatively analyzing the
output signals from at least two spatially adjacent light-detector subelements to
establish a data set reflective of an extent to which output signals responsive to the
image of the feature are produced from exactly one or from more than one of the
adjacent light-detector subelements, and to reach a conclusion from the data set as to a
location, of the image of the feature on the segmented light-detector array with an
accuracy of less than the linear dimension when the, output signal is produced from
more than one of the adjacent array subelements. However, determining feature
locations and cooperatively analyzing adjacent array subelements, for document
generation or document reproduction devices such as digital scanners, copiers and
facsimile machines would be routinely performed by any appropriate software or
microprocessing function within the device in order to convert and place the detected
signals in the proper location in the device's memory. For example, the microprocessing
functions performed by the "CMOS active pixel color linear image sensor" in Fig. 3 of
Ang (U.S. Patent No. 6,507,011 B2) such as line control/readout logic circuit (320), line
store select logic (330), timing control circuit (370) and analog mux (350).. It would have
been obvious to one skilled in the art to provide a device capable of cooperatively
analyzing adjacent array subelements and determining feature locations for the purpose
of reconstructing (from memory) the imaged feature for image reproduction.

Regarding claim 19, Hou shows in Fig. 10, the step of providing a sensor includes the step of providing a one-dimensional segmented light-detector array having non-spatially overlapping light-detector subelements.

Response to Arguments

7.   Applicant's arguments filed 03/31/2008 have been fully considered but they are not persuasive.

In response to applicant's arguments that Vock neither describes nor suggests the limitations emphasized on page 13, lines 9-17 of the remarks, the examiner disagrees. Vock clearly describes in col. 3, lines 13-25 imaging an object (golf ball) at high frame rates "frame rates will capture a golf ball at each frame and at adjacent pixels frame-to-frame" and subsequently analyzing the image of the golf ball frame-by-frame "when the composite image is analyzed....making distance determination relatively easy". Vock clearly describes analyzing adjacent pixel data (particularly representing the golf ball) at least among frames to determine the golf balls position at a particular time. In addition, Vock also describes in col. 7, lines 33-40, utilizing certain digital electronics to perform tracking and detecting a moving object (golf ball) within a given range using the data from selected pixels from each frame to determine object motion, location, flux intensity and distance. Therefore Vock describes operations with sufficient particularity to determine whether all claimed operations are performed.

In response to applicants arguments regarding claim rejections of 1 and 13 under 35 U.S.C. 103(a) with respect to Perregaux (U.S. Patent No. 6,654,056 B1) and Hou

(U.S. Patent No. 6,596,979 B2), an additional reference has been provided as an

example for further support of these rejections.

Conclusion

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Kevin Wyatt whose telephone number is (571)-272-

5974. The examiner can normally be reached on Monday-Friday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Georgia Epps can be reached on (571)-272-2328. The fax phone number

for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the

Patent Application Information Retrieval (PAIR) system. Status information for

published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only.

For more information about the PAIR system, see http://pair-direct.uspto.gov. Should

you have questions on access to the Private PAIR system, contact the Electronic

Business Center (EBC) at 866-217-9197 (toll-free).

/K. W./
Examiner, Art Unit 2878

/Thanh X Luu/

Primary Examiner, Art Unit 2878